

Concrete Kibble

Warning

Safe working load (SWL) must not be exceeded.

Pre-use inspection

Inspect Machine

- Ensure welds upon the kibble are free of cracks or other deformations

Inspect Workplace

- Ensure that the area in which the kibble is going to be used is clear and free from any obstructions that could lead to injury/damage to personnel/property

Operating Instructions

- Before loading any material into kibble ensure discharge gate is fully closed.
- To lift kibble attach crane hook to the top point of the kibble and proceed to lift slowly
- To open discharge gate, pull the kibble handle downwards always closing the gate by the reverse action once enough material has been poured

Safety Instructions

- A competent person with a 'worksafe' dogging or rigging certificate should normally operate the kibble.
- Operator MUST ensure that at NO TIME do personnel ride or be in the kibble
- The extremity of the fork arms shall not be used as a lever to lift a load
- Maintain relevant clearance of electrical conductors

For the complete operators manuals please feel free to ask at the counter for a copy

Hazard Identification and Risk Assessment		
Hazards Identified	Injury	Risk Control Measure in place
Kibble falling off hook	Death Crushing Severed limbs	Ensure kibble is securely located on crane/forklift and maintain a constant distance from kibble while elevated. Ensure Crane is weighted greater than that of the kibble
Pinching Hazard	Severed fingers	While pulling down handle to open or shut discharge gate ensure limbs stay away from all gaps